

Birch Faced

PRODUCT DATA SHEET






Plywood constructed with outer faces of birch veneers with poplar comprising the inner layers.

Our  Hanson Lightweight Panguaneta Plywood offers stability, ease of cutting and combines higher mechanical properties with the benefits of a lightweight panel.

Poplar/birch combi core is available on request. Outer faces are available in both long and cross grain directions. Birch faced poplar plywood is manufactured in accordance with the European and International standards.

Applications

-  Automotive
-  Furniture and design
-  Shop/Bar fitting
-  Boat/Yacht building
-  Construction, architecture and general joinery

SPECIFICATION DETAIL:

Thicknesses (mm)	6mm-40mm
Dimensions	2440 x 1220 3050 x 1220
Average Density	400 Kg/m ³ ± 10%
Manufactured to	EN 636-1
Glue Bond	Class 1 (Interior) EN 314-2
Formaldehyde Release	Class E1 (Tested to EN 717-2)
Veneers	High quality face and core
Face Grade	B/BB
Environmental Certification	PEFC (FSC available on request)
European Timber Regulation (EUTR) status	Compliant - Sourced within EU
CE Marked	BS EN 13986
Material Safety Data Sheet	Available

CONTACT:

Drakes Industrial Estate
Shay Lane, Halifax
West Yorkshire
HX3 6RL

Tel: 01422 330444
Fax: 01422 330706
Email: sales@hanson-plywood.co.uk
www.hanson-plywood.co.uk

For more information visit: www.hanson-plywood.co.uk

