

# The Plywood Specifiers Guide

Structural



Multi-use structural hardwood plywood suitable for a wide range of industries.

## Structural plywood

- ✓ EN 636-3 S (may require further treatment depending on application)
- ✓ Glue bond: EN 314-2 Class 3
- ✓ CE Marked for performance in all conditions
- ✓ Suitable for use as structural components in exterior conditions
- ✓ FSC® Certified
- ✓ A safe and correct choice for architects and specifiers



CONSTRUCTION, ARCHITECTURE, JOINERY



VEHICLE BODY BUILDING



THEATRE SETS



BOAT BUILDING



FLOORING & ROOFING



PORTABLE BUILDINGS



FURNITURE



SHOP & BAR FITTING



PACKAGING



LOADING PLATFORMS



## PRODUCT TECHNICAL DATA



### SPECIFICATION DETAIL:

Manufactured to	EN 636-3 S (may require further treatment depending on application)
Glue bond	EN 314-2 Class 3 (Exterior)
Size	2440mm x 1220mm
Thickness	4mm, 6mm, 9mm, 12mm, 18mm, 25mm
Formaldehyde release	Class E1
Moisture content	10% ( $\pm 2$ )
Veneers	High quality face and core
Average density	500 kg/m <sup>3</sup> - 550 kg/m <sup>3</sup>
Environmental and legality	FSC® Certified
CE Marked	BS EN 13986
Material Safety Data Sheet	Available

The product is from sustainable, legal and responsible FSC® Certified forest management units.

# Notes



---

**CONTACT:**

Hanson Plywood Limited  
Drakes Industrial Estate  
Shay Lane, Halifax  
West Yorkshire, HX3 6RL

Tel: 01422 330444

Fax: 01422 330706

Email: [sales@hanson-plywood.co.uk](mailto:sales@hanson-plywood.co.uk)

[www.hanson-plywood.co.uk](http://www.hanson-plywood.co.uk)

For more information visit: [www.hanson-plywood.co.uk](http://www.hanson-plywood.co.uk)

